

## LEAN Thinking Analysis of Fastener Installation in Metal Stampings

Rob Edwards

PROFIL, VP Business Development

# The Discussion

## Value Stream Analysis of

Traditional projection  
weld nut installation



vs

Mechanically Attached  
Fasteners (MAF) in-die  
installation



## Part Information

200,000 EAU

RH & LH Bracket per vehicle

225 MPa steel

(2) M6 nuts per Bracket

## Stamping Process

600-ton press

RH & LH out prog die

## Projection Weld Nut Process

Projection weld nuts

Pedestal weld

Nuts auto feeding

(2) Nuts installed per welder cycle

Panel manually loaded & unloaded

## In-Die Rivet Nut Process

Mechanically Attached nuts

In-die installation

Nuts auto feeding

(4) Nuts installed per press cycle

Nut feeding to 60 SPM


Right Hand



Left Hand



# Waste





# MUNRO Analysis – Side-by-Side Summary

GDIS

Cost Element
Fasteners
Process Steps
Total Cycle Time (sec)
Purchased Part Roll up Costs
Raw Material Costs
Processing Costs
<b>Total Manufacturing Cost (without Mark-Up)</b>
SG&A Applied to Manufacturing 12%
Logistics Applied to Sum of all Above 3%
<b>Total Cost without Tooling Amortization</b>
Profit Mark-Up 8%
Tooling and Equipment Amortization
<b>Sale Price</b>
Total Tooling Investment
Tooling Cost / LH&RH Pair Set

Projection Weld Nuts	In-Die Rivet Nuts
4	4
28	10
24	2
\$ 0.24	\$ 0.32
\$ 2.36	\$ 2.36
\$ 0.39	\$ 0.05
<b>\$ 3.00</b>	<b>\$ 2.73</b>
\$ 0.36	\$ 0.33
\$ 0.10	\$ 0.09
<b>\$ 3.46</b>	<b>\$ 3.15</b>
\$ 0.31	\$ 0.29
\$ 0.32	\$ 0.35
<b>\$ 4.09</b>	<b>\$ 3.79</b>
\$ 389,188	\$ 421,533
\$ 0.32	\$ 0.35

**Piece Price Save per Pair of Brackets (4 nuts)**  
**Life of Program Save**

\$ 0.30      **\$.075 per installed fastener**  
\$ 359,254

← **Shorter process, Think LEAN**  
← **Shorter process, Think LEAN**

Program Information	
Vehicle Annual Volume	200,000
Years of Production	6
Efficiency	85%
Production Location	USA

Costing is per set of Brackets



# MUNRO Analysis – Side-by-Side Detail

GDIS

## Projection Weld Nuts

Purchased Parts							
Part Name	Material	Total Quantit	Weight (kg)		Piece Cost Each	Notes	Total Cost
Weld Nut-M6 x 1.00-Flanged Hex Head		4	0.0069		\$0.06		\$0.24
Sub Totals		4	0.0069		\$0.06		\$0.24

## Purchased Parts

Purchased Parts							
Part Name	Material	Total Quantit	Weight (kg)		Piece Cost Each	Notes	Total Cost
PROFIL M6 RND Rivet Nut		4	0.0069		\$0.08		\$0.32
Sub Totals		4	0.0069		\$0.08		\$0.32

+\$.08

Raw Materials							
Part Name	Material	Total Quantit	Net Weight kg	Gross Weight kg	Material Cost Per kg	Piece Cost Each	Notes
LH Heat Pump Mtg Bracket	Med Carbon Steel 1040	1	0.4824	0.8260	\$1.43	\$1.18	LH & RH Out at the same time during the stamping. The material cost includes both
RH Heat Pump Mtg Bracket	Med Carbon Steel 1040	1	0.4824	0.8260	\$1.43	\$1.18	
Sub Totals		2	0.9648				\$2.36

## Raw Materials

Raw Materials							
Part Name	Material	Total Quantit	Net Weight kg	Gross Weight kg	Material Cost Per kg	Piece Cost Each	Notes
LH Heat Pump Mtg Bracket	Med Carbon Steel 1040	1	0.4824	0.8260	\$1.43	\$1.18	LH & RH Out at the same time during the stamping. The material cost includes both
RH Heat Pump Mtg Bracket	Med Carbon Steel 1040	1	0.4824	0.8260	\$1.43	\$1.18	
Sub Totals		2	0.9648				\$2.36

+\$.00

Processing - 2 Weld Nuts per Panel							
Process Description	Process Steps	Total Quantit	Work Cell Machine Rate Cost/Hour	Number of Operators	Labor Rate Cost/Hour (Fully Burdened)	Total Time (Sec)/Part	Notes
LH & RH Bracket Stamping							Cycle Time per part includes Tooling Changeover amortizing time, stamping press cycle time.
600 Ton Progressive Stamping		1	\$46.43	0.5	\$42.67	1.06	LH & RH are stamped at same time. So the time per part is reduced to half of the total cycle time.
600 Ton Progressive Stamping		1	\$46.43	0.5	\$42.67	1.06	LH & RH are stamped at same time. So the time per part is reduced to half of the total cycle time.
LH & RH Nuts Assembly Process							Assume one pedestal welder, one panel and two nuts welded per cycle, weld fixture common for RH & LH panels
LH Panel Projection Welding		1	\$10.75	1	\$40.42	8.00	
EMP Fixture Gage Off Line C		1	\$0.00	1	\$40.42	3.00	
RH Projection Welding		1	\$10.75	1	\$40.42	8.00	
EMP Fixture Gage Off Line C		1	\$0.00	1	\$40.42	3.00	
Sub Totals							\$0.39

## Processing

Processing - 2 PROFIL MAF Nuts per Panel							
Process Description	Process Steps	Total Quantit	Work Cell Machine Rate Cost/Hour	Number of Operators	Labor Rate Cost/Hour (Fully Burdened)	Total Time (Sec)/Part	Notes
LH & RH Bracket Asm In-Die Mechanically Fastened Nuts Stamping							Cycle Time per part includes Tooling Changeover amortizing time, stamping press cycle time.
600 Ton Progressive Stamping		1	\$50.48	0.5	\$42.67	1.06	LH & RH are stamped at same time. So the time per part is reduced to half of the total cycle time.
600 Ton Progressive Stamping		1	\$50.48	0.5	\$42.67	1.06	LH & RH are stamped at same time. So the time per part is reduced to half of the total cycle time.
Sub Totals							\$0.05

-\$ .34  
-\$ .26

Tooling - 2 Weld Nuts per Panel							
Part Name	Process	Total Quantit	Cost Each			Notes	Total Cost
LH & RH Heat Pump Mtg Bracket	Progressive Stamping Die	1	\$313,593			LH & RH Out Progressive Stamping Die to form the LH & RH Bracket	\$313,593
LH & RH Heat Pump Mtg Bracket Asm	Assembly & Quality Check						\$0
	Projection Welding Nuts	1	\$66,600			Proline Pedestal Welder, Dual Heads	\$66,600
	EMP Fixture Check	1	\$8,995			Fixture Cost	\$8,995
Sub Totals							\$389,188

## Tooling

Tooling - 2 PROFIL MAF Nuts per Panel							
Part Name	Process	Total Quantit	Cost Each			Notes	Total Cost
LH & RH Heat Pump Mtg Bracket	Progressive Stamping Die	1	\$313,593			LH & RH Out Progressive Stamping Die to form the LH & RH Bracket	\$313,593
LH & RH Heat Pump Mtg Bracket Asm	Progressive Stamping Die w/2 Nut In-Die Tooling						\$0
	2-Nut In-Die Tooling	2	\$22,720				\$45,440
	4-Tracks Nut Feeder	1	\$62,500				\$62,500
Sub Totals							\$421,533

+\$32,345

**\$.07 to \$.15 save per installed fastener**


**400 structural fasteners per vehicle**

**\$30 to \$60 per vehicle**


***Think LEAN ... Think In-Die***

# Soft Costs

GDIS



**Weld**



**MAF**  
**In-Die**

**Perishables**

Shunts  
Electrodes

**Floor Space**

Weld cell  
WIP storage

**Consumable**

Conditioned electricity  
Chiller (cooling water)  
Compressed air

**WIP**

Cost of inventory  
Material moves in plant  
Scheduling

**Maintenance**

Air scrubber  
Clean feeder bowls

**Racks**

WIP racks needed

**Perishables**

Die button (500k hits)

**Consumable**

Compressed air

**Maintenance**

Inspect die buttons  
Clean feeder bowl

# LEAN Principles Realized

GDIS

1

## Value

Eliminate waste and costs to meet the optimal price for the customer and maximize profits

2

## Value Stream

Analyzing materials and resources required identifying waste and improvements

3

## Flow

Removing barriers to improve lead times

4

## Pull

Working by only doing work when there is demand

5

## Perfection

Continued process improvements

# In-Die Methods and Technologies

GDIS

## Stamping Process

Prog

Transfer

Tandem

## Fasteners

Nuts

Studs

## Orientation

Top - Down

Bottom - Up

## Press Speeds

Nuts up to 60 SPM

Studs up to 40 SPM

## Feeders

Up to 20' from die

Multiple ganged



Not stamping  
specific

Out of press  
On bolster

# In-Die Methods and Technologies

GDIS


Installation Method	In-Die - progressive
Insert Direction	Top to Bottom



# In-Die Methods and Technologies

GDIS




Installation Method	In-Die - progressive
Insert Direction	Top to Bottom + Bottom to Top



# In-Die Methods and Technologies



GDIS

Installation Method	In-Die - progressive
Insert Direction	Bottom to Top



# In-Die Methods and Technologies

GDIS




# Application Engineering

# Application Engineering

# In-Die Methods and Technologies

GDIS



## Press + Installation Tool & Equipment Interface

- Press to installation equipment interface is one die protection signal, no press controls changed
- Installation control is fully managed and error-proofed in feeder equipment
- PROFIL takes ownership of installation controls

- 480 VAC / 30A
- 75 psi compressed air
- Handshake signal from press

There is a better way

*Think LEAN ... Think In-Die*

# Thank You for Your Attention

Danke, Gracias, Dziękuję Ci, Merci, Grazie

Děkuji, 감사합니다, ありがとう

## For more information

Rob Edwards

PROFIL

[redwards@pemnet.com](mailto:redwards@pemnet.com)